



Installation slide rail ECO IS EF

ECO IS EF

Slide rail ECO IS EF with electromagnetic hold-open device for ECO ITS Multi-Genius

- **Slide rail height:** 21 mm
- **Slide rail length:** 550 mm
- **Same model:** DIN L and DIN R
- **Power consumption:**
24 V DC maximum 1.8 W
- **The scope of delivery includes:**
slide rail ECO IS EF
fixing accessories

■ Slide rail IS EF:

In combination with ECO ITS Multi Genius, tested acc. to **EN 1155**, approved for use on fire and smoke control doors, and in combination with ECO RSZ approved for use by the DIBt as a hold-open system.

■ Electromagnetic hold-open device:

Adjustable from 70° to 110°. In the event of fire, the hold-open device is overridden and the door closer is triggered to close the door. It is controlled by the external smoke control centre ECO RSZ

Slide rail ECO IS EF	Profile	Art. no.
ECO IS EF (L = 550 mm)	31 x 21 mm	5030054384

Delivery without lever arm, this is part of the door closer

Note!
For more information on milling dimensions and mounting instructions, please visit www.eco-schulte.de.



ECO Schulte GmbH & Co. KG

Iserlohner Landstraße 89

D-58706 Menden

Telephone +49 2373 9276 - 0

Telefax +49 2373 9276 - 40

info@eco-schulte.de

www.eco-schulte.de

Our compendium represents a compilation of all products from our range of services. These are subject to different delivery classes. Special variants included are often manufactured to customer specifications and sometimes require longer delivery times and minimum purchase quantities. Further advise can be given by your contact person.

■ SYSTEM TECHNOLOGY FOR THE DOOR

