

ECO SR-R III

Door coordinator with continuous cover hood and integrated smoke detector. For the connection of ECO FTS III or external magnetic door clamps (THM).

■ **Compatible for the connection of:**

ECO FTS III or external holding magnets as per DIBt BAG (see accessories and DRM ORS 142, TDS 247)

■ **Controlled via:**

Integrated smoke detector with power supply unit. Connection: 230 V AC, IP 10, protection rating I

■ **Area of application:**

-15 to +45 °C, relative humidity max. 95%

■ **Minimum size passive leaf:**

360 mm (for TS-41) or 400 mm (for TS-61)

■ **Delivery:**

Incl. matching cover profile, without lever arm, this is part of the door closer

■ **Installation of the system:**

Only on the hinge side

■ **The use of the ECO MK 1 driver flap is required for full panic doors.**

■ **Slide rails door coordinator:**

Ensures that the closing sequence of the passive and active leaf is in the prescribed order, i.e. the active leaf always closes after the passive leaf.

■ **Electromagnetic hold-open device via FTS III or external THMs:**

The system (IBO) is kept open by external THMs or the free swing closer ECO FTS III (on GF). This allows a hold-open angle of up to 175° (depending on the frame construction and on-site conditions).

■ **Tested according to: EN 1155 and EN 1158 and approved by the DIBt.**

Door coordinator ECO SR-R III

Hinge gap scope of delivery (set) 1,641-2,645 mm

For larger hinge gaps, 2,645-2,800 mm, please also order the extended connection rod VBS ECO SR III.

DIN L	Colour	Art. no.
ECO SR-R III (Si)	Silver RAL 9006	5030054433
ECO SR-R III (W)	White RAL 9016	5030056143
ECO SR-R III (S)	Black RAL 9005	5030056145
ECO SR-R III (ER M)	Matt stainless steel	5030053698


DIN R	Colour	Art. no.
ECO SR-R III (Si)	Silver RAL 9006	5030054450
ECO SR-R III (W)	White RAL 9016	5030056146
ECO SR-R III (S)	Black RAL 9005	5030056148
ECO SR-R III (ER M)	Matt stainless steel	5030056149

Note!
Please order the corresponding accessories for the different mounting versions at the same time.



ECO mounting versions – hinge side


Direct installation



Direct installation is the standard mounting type for ECO. The slide rail is mounted directly on the frame. The ECO fixing holes must be prepared for this purpose.

A paper drilling template is included in all packaging. In addition, a metal drilling template or corresponding drilling dimensions are also available as a PDF or DXF file (www.eco-schulte.de).


Installation with standard profile (ADP)



Installation with standard profile (ADP 20) is used if the frame has already been prepared with the mounting hole dimension 120/428.5 mm, e.g. for steel frames or for replacement/retrofitting.

The standard profile is mounted directly on the frame and adapts the ECO drilling dimension to this pre-prepared dimension. It can be ordered separately as an accessory.

Installation with adaption profile (ADP 30)



The adaption profile (ADP 30) is used if the frame construction does not allow stable fixing of the slide rail, e.g. for steel frames with rebated doors.

The adaption profile is mounted directly on the frame. The slide rail can now be mounted stably on this ADP.

It can be ordered separately as an accessory.

The drilling dimensions for the adaption profile are included on the enclosed paper drilling template. In addition, a metal drilling template or corresponding drilling dimensions are also available as a PDF or DXF file (www.eco-schulte.de).

ECO Schulte GmbH & Co. KG

Iserlohner Landstraße 89

D-58706 Menden

Telephone +49 2373 9276 - 0

Telefax +49 2373 9276 - 40

info@eco-schulte.de

www.eco-schulte.de

Our compendium represents a compilation of all products from our range of services. These are subject to different delivery classes. Special variants included are often manufactured to customer specifications and sometimes require longer delivery times and minimum purchase quantities. Further advise can be given by your contact person.

■ SYSTEM TECHNOLOGY FOR THE DOOR

