







Standard door openers

Red/operating current (closed without power)

Standard door openers			<ul style="list-style-type: none">▪ Radius latch▪ Closed without power▪ Momentary contact: 10–24 V AC/DC▪ Continuous operation: 12VDC (11.5...13VDC)▪ DIN left / DIN right independent▪ Adjustable latch bolt: 3 mm▪ Latch bolt depth: 5.1 mm▪ Locking force: 3230 N▪ Max. latch bolt preload at 12VAC: 250 N▪ Max. latch bolt preload at 24 VAC: 360 N▪ Max. latch bolt preload at 12VDC (stabilised): 50 N
Standard door opener 12V ASP RF B3000--K		5030067787	<ul style="list-style-type: none">▪ Dimensions: Height 66 mm, width 16 mm, depth 25.5 mm▪ Includes bipolar protective diode
Standard door opener 12V ASP RF B3000-TK		5030067788	<ul style="list-style-type: none">▪ Dimensions: Height 66 mm, width 20.1 mm, depth 25.5 mm▪ Includes bipolar EMC protective diode▪ Top latch bolt guidance
Standard door opener 12V ASP RF TK B3001--K		5030067789	<ul style="list-style-type: none">▪ Dimensions: Height 74 mm, width 16 mm, depth 25.5 mm▪ Includes micro switch as a door monitoring contact (door contact)▪ Includes bipolar protective diode
Standard door opener 12V ASP RF TK Top B3001-TK		5030067790	<ul style="list-style-type: none">▪ Dimensions: Height 74 mm, width 20.1 mm, depth 25.5 mm▪ Includes micro switch as a door monitoring contact▪ Includes bipolar EMC protective diode▪ Top latch bolt guidance
Standard door opener 12V ASP RF E B3010--K		5030067791	<ul style="list-style-type: none">▪ Dimensions: Height 66 mm, width 16 mm, depth 25.5 mm▪ Includes mechanical unlocking▪ Includes bipolar protective diode
Standard door opener 12V ASP RF E Top B3010-TK		5030067793	<ul style="list-style-type: none">▪ Dimensions: Height 66 mm, width 20.1 mm, depth 25.5 mm▪ Includes mechanical unlocking▪ Includes bipolar EMC protective diode▪ Top latch bolt guidance

Note: All standard openers are not approved for fire protection, only smoke protection.
All standard door openers are also available in a 24 V version on request.

ECO Schulte GmbH & Co. KG

Iserlohner Landstraße 89

D-58706 Menden

Telephone +49 2373 9276 - 0

Telefax +49 2373 9276 - 40

info@eco-schulte.de

www.eco-schulte.de

Our compendium represents a compilation of all products from our range of services. These are subject to different delivery classes. Special variants included are often manufactured to customer specifications and sometimes require longer delivery times and minimum purchase quantities. Further advise can be given by your contact person.

■ SYSTEM TECHNOLOGY FOR THE DOOR

